



519.00 EUR

incl. 19% VAT, plus [shipping](#)

- Replace JNC9KDL-2700 !

Support: [Specifications \[EN\]](#)

- INTEL® Cedar Trail-D Processor D2550 + NM10 Chipset
- Support 2 \* DDR3 800/1067MHz Single CH up to 4GB
- Support DirectX 9 Graphics
- Support 2 \* Serial ATAII (3Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 6-CH
- 1 \* 24 bits Single Channel LVDS header
- Supports 2 \* Realtek RT8111EVL Gigabit LAN
- Support Watch dog Technology
- Support CPU Smart FAN
- Compliance with ErP standard
- Mini-ITX Form Factor (170mm x 170mm)
- **CPU**
  - INTEL® Cedar Trail-D Processor D2550 CPU (1.86GHz)
- **Chipset**
  - INTEL®NM10 Express chipset
- **Memory**
  - 2 \* DDR3 1067MHz Single CH SO-DIMM up to 4GB
- **Expansion Slots**
  - 1 \* PCI slot
- **Storage**
  - 2 \* Serial ATA2 3Gb/s connectors
- **Audio**
  - Realtek ALC662 6-Channel HD Audio
- **Ethernet LAN**
  - 2 \* RTL8111EVL PCI-E Gigabit LAN
- **LVDS**
  - Onboard 24-bits single channel connector
- **USB**
  - Embedded 8 \* USB 2.0/1.1
  -
- **Special Features**
  - Support ACPI S3
  - Support CPU Smart FAN
  - Support Watch Dog

- **Rear Panel I/O**
  - 4 \* USB 2.0/1.1 ports
  - 1 \* PS/2 Mouse & 1 \* Keyboard connector
  - 2 \* RJ-45 port
  - 3 \* Audio I/O ports ( Line-in, MIC and Line-out )
  - 1 \* VGA port
  - 1 \* HDMI port
- **Internal I/O**
  - 2 \* USB 2.0/1.1 headers for 4 USB 2.0 ports
  - 2 \* NB / Chassis Fan connectors;
  - 1 \* 24-pin ATX Power connector
  - 1 \* LVDS header/1 \* Inverter header
  - 1 \* AUDIO header
  - 1\* RS232 header
  - 1 \* Parallel header
- **BIOS**
  - AMI 16MB DIP Flash ROM
- **Functional**
  - ATM, Automation, Medical Equipment, Digital Signage, Networking, POS, General Application, Transportation
- **Packing**
  - Color Box Dimension■200(W) x 200(D) x 70(H)mm
- **Certificate**
  - CE, FCC, RoHS
- **Temperature**
  - Operating within 0~40 centigrade (**Suggest to use system FAN**)
  - Storage within -20-85 centigrade
- **Form Factor**
  - Mini ITX Form Factor(17cmx17cm)

**Product Accessories**

- COM cable
- Manual
- CD
- 2x SATA cable
- I/O shield