59.95 EUR
incl. 19% VAT, plus shipping

- M.2 NGFF !
- UMTS / 3G !
- LTE (EUROPE) !

Support: Specifications | Drivers (Windows) | Dialer Software

The ME906E is a LTE module with NGFF interface , supporting LTE (FDD) B1/B2/B3/B5/B7/B8/B20,Penta-band DC-HSPA+/HSPA+/HSPA/WCDMA for Europe network coverage, low power consumption, Global Navigation Satellite System(GNSS), and European carrier certifications, enabling easier and more flexible design and integration into end devices. In addition, the ME906E supports NGFF features to optimize performance, power consumption, and usability.

ME906E is the ideal choice for Ultrabook, notebook, tablet etc.

Manufacturer	Huawei
Model	ME906E
Unlocked	Ready for use with global services. No contract required.
Network Bands	• LTE (FDD) B1/B2/B3/B5/B7/B8/B20 Quad-band DC-HSPA+/HSPA+/HSPA/UMTS B1/B2/B4/B5/B8 Quad-band EDGE/GPRS/GSM 1900/1800/900/850 MHz
Data Speed	GPRS/EDGE: Multi-slot Class 12 WCDMA PS: UL (384 kbps)/ DL (384 kbps) DC-HSPA+ :UL (5.76 Mbps)/ DL (42 Mbps) LTE FDD: UL (50 Mbps)/ DL (100 Mbps) @Bandwidth 20M (CAT3)
Interface	Antenna interfaces x 2 M.2 Socket 2 USB 2.0 interface high speed Power supply UICC interface
Power Supply	Supply voltage range:3.135V~4.4V (3.3 V recommended)
Temp Range	Normal operation: -10°C to +55°C Extended operation: -20°C to +70°C Storage: -40°C to +85°C
GPS	GNSS: GPS Standalone, A-GPS, GPS XTRA, Glonass
Dimensions	• 42x30x2.3 mm

Supported Systems	Windows 7/Windows 8/Android 4.0 or above
Special Features	SIM Hotswap IPV6 BodySAR Ultrabook feature support(ACT, WiFi Offload , DPTF) Tunable Antenna Supporting MO and MT Supporting formats of PDU Point-to-point and cell broadcast
Package Contents	New Huawei ME906E NGFF Embedded Module.