

609.00 EUR
incl. 19% VAT, plus [shipping](#)



Support:  [Specifications](#)

Chip	Broadcom
Dimensions	140x138x60mm
Certifications&Safety	CE, FCC, ROHS
	8x 10/100/1000BaseT(X)
I/O Ports	4x 1000 BaseSFP
	RS-232(RJ45) Console port
	LED: Power, POE, port speed, port connection
Management	Support WEB Interface
	Support SNMP v1/v2/v3
	IEEE802.3 10Base-T Ethernet standard
	IEEE802.3u 100Base-TX/FX
	IEEE802.3z 1000Base-X
	IEEE802.3ab 1000Base-T(X)
Standards	IEEE802.3x Flow control
	IEEE802.1d STP
	IEEE802.1w RSTP
	IEEE802.1s MSTP
	IEEE802.1p QoS
	IEEE802.1ad QinQ
	10BASE-T: Category 3 and above non-mask / mask twisted pair (<=100 m)
Network interface / Wire specifications	100BASE-TX: Category 5 and above non-mask / mask twisted pair (<=100 m)
	1000BASE-T: Category 5 and above non-mask / mask twisted pair (<=100 m)
	PoE standard: IEEE802.3af, IEEE802.3a
PoE Support	Each port provides 15.4W, maximum 30W
	Pin Definition: V+ (RJ4S Pin 1, 2), V- (RJ4S Pin 3, 6)
	PoE Management: Support port-based PoE status display and PoE switch control

Power input / consumption	Input voltage 45-60VDC Redundant dual power input Reverse connection protection Power interface : 5pin terminal Power supply : 140W (max)
Operating temperature	-40~75°C
Cooling	Fanless
MTBF	100.000hrs