



829.00 EUR
incl. 19% VAT, plus [shipping](#)

- 10.1" 400 nits high brightness TFT LCD with LED backlight
- 10-points Multi Capacitive Touch
- Cable less, Streamlined enclosure for highly efficient heat dissipation Enclosed in robust aluminum casing
- Edge-to-edge narrow bezel design and Fanless cooling system
- Design for easy Wall mount, Panel Mount, VESA Mount installation
- A true Flat, easy-to-clean front surface with edge-to-edge design
- Lockable USB device bracket supported
- Front bezel meets IP65-rated protection
- 9-28V DC-input Support, with EOS, OVP design

Jetway HPC101SC-FP1900B Flat-Panel Fanless Panel PC provides outstanding outlook with industrial-grade quality for comprehensive industrial markets, such as retails, wholesales, hospitality, hospital or meeting room registration, logistics, self-service kiosk, residential automation and digital signage.

Jetway HPC101SC-FP1900B Flat-Panel Fanless Panel PC is designed with 10-points Multi capacitive type touch screen. High brightness TFT LCD panel with LED backlight are equipped with this model. Cable-free design is easy for the HDD and memory installation. Streamlined enclosure with narrow bezel design.

Jetway HPC101SC-FP1900B Flat-Panel Fanless Panel PC is designed with a true flat, easy-to-clean front surface with edge-to-edge design. It is designed mounting clips for easy Wall mount, Panel Mount, VESA Mount installation.

Front bezel meets IP65-rated & NEMA 4 protection. Welcome to use Jetway Flat-Panel Panel PC.

Display	
Front Bezel	– IP65, NEMA 4 rugged protection, Full planar metal border
Display Type	– 10.1" With LED Backlight
Brightness (cd/m ²)	– 400 nits

Display Color	– 16.2M
Resolution	– 1280 x 800 @ 60Hz
Viewing Angle (H/V)	– 170°/170°
Pixel Pitch	– 0.1695 x 0.1695 mm
Aspect Ratio	– 16:10
Contrast Ratio	– 800:1
Response Time	– 30 ms
Touch Screen	
Type	– projected capacitive type
Active Range	– 257.10 x 159.66mm ±0.2mm
Transparency	– ■87%
Surface Hardness	– ■6H (JIS-5400)
Glass haze value	– ■3%
CASE	
Panel Material	– Aluminum
Case Material	– Iron
Color	– Silver + white
Coating Requirement	– Spray Paint
Main System	
CPU	– Intel® Bay Trail-D J1900 2.0GHz/QC
RAM	– 4G 1333MHz DDR3L SAMSUNG DRAM
BIOS	– 64MB SPI Flash ROM
Storage	– 1* 2.5" SATA bay
	– 1* M.2 connector (2242/2260/2280)
Watchdog Timer	– 256 levels, 0~255 sec.
OS Support	– Windows 7 / 8.1 / 10 / Linux (Option)
I/O Connector	
I/O Ports and Switches	– 2 * USB3.0
	– 2 * USB2.0
	– 1 * 8bit GPIO
	– 2 * RS232/422/485
	– 1 * VGA
	– 2 * LAN (INTEL I211AT Gigabit LAN)
	– 1 * Locking Jack 9~28V DC input
	– 1 * Power button
Expansion Interface	
Expansion	– 1 * PCI-E mini card for WIFI or 3G/4G
Power	
Power Input	– Supports 9-28V DC Power in with over current protection fuse
	– Provides 100~240V AC-DC 12V, 60W power adapter
Power Consumption	– 21W
Dimension	
Case Dimensions	– 258.96*176.60*59.7mm
Certifications	
Certifications	– CE, FCC, IP65(Front)
Environment	

Temperature	– Operating Temperature: -10 ~ 60° C (with W.T. DRAM/HDD in airflow condition) – Storage Temperature: -20 ~ 85° C
Shock	– Operating: 15G■11ms duration
Vibration	– Operating: 5~500Hz/1 Grms
Warranty	
Warranty	– 2 Years Limited Warranty(Panel and Touch is only Warranty 1 Year)