



79.95 EUR
incl. 19% VAT, plus [shipping](#)

- Applied 100% Solid capacitor design to maximize component reliability
 - ECS Durathon Technology ensure the stability, reliability and performance of system.
 - ESD Protection prevents computers from electrostatic discharge damage to enhance its durability and lifespan
 - ECS MIB III - A friendly interface for overclocking
 - DC-in power jack
 - Supports DirectX® 12 to enhance graphical performance
 - Supports Intel® HD Graphics
 - Supports HDMI 1.4a Technology (resolution up to 1920X1200) and HDCP function
- Supports Intel® CNVi

CPU

Onboard Intel® Apollo
Lake processors
100% Solid capacitor
design

GRAPHICS

Supports DirectX® 12
Supports HDMI 1.4b &
Premium Audio

MEMORY	Dual-channelDDR3L
	Memory architecture
	Supports DDR3L 1066
	non-ECC, Un-buffered SO
EXPANSION SLOT	DIMM Memory
	2 X DDR3 SO-DIMM
	socket
	Support up to 8 GB*
Storage	1 X M.2 slot for 2242/2280 SSD
	1 X M.2 slot for WiFi/BT PCIe Gen 2
	2 X Serial ATAIII 6Gb/s
	6-Channel HD audio
Audio	CODEC Realtek ALC662
	Realtek ALC662 6-channel
	High Definition audio
	CODEC
	Meets performance
	requirements for Microsoft
	WLP 3.08 Vista premium
	and mobile PCs
	Six channel DAC supports
	16/20/24-bit PCM format
	for 5.1 channel audio
	solution
LAN	Emulation of 26 sound
	environments to enhance
	gaming experience
	Voice Cancellation and
USB	Key Shifting in Karaoke
	mode
	Compatible with Direct
	Sound 3D™, A3D™,
REAR PANEL I/O	I3DL2
	Realtek 8111H Gigabit
	Fast Ethernet Controller
	4 X USB3.1 Gen1 port(s) up to 5Gb/s (either rear I/O or front header)
	6 X USB2.0 port(s) Up to 480 Mb/s [Back Panel 2 port(s), Onboard 4 port(s)]
	1 X PS/2 Keyboard & PS/2
	mouse connectors
	1 X Audio port (Line
	Out/Line In/Mic In)
	1 X RJ-45 port
	1 X HDMI port(s)
	1 X D-Sub (VGA) port(s)
	1 X Display port(optional
	instead of D-SUB (VGA))
	2 X USB3.1 Gen1 port(s)
	2 X USB2.0 port(s)
	1 X DC-in 19V Connector

CONNECTORS & HEADERS	1 X 4-pin SYS_FAN connector
	1 X Front Panel MIC/Speaker out header
	1 X Front panel audio header
	1 X USB 3.1 Gen1 header (Support additional 2 USB ports)
	2 X USB 2.0 header (Support additional 4 USB ports)
	1 X CLR_CMOS header
	2 X Serial port header (COM)
	1 X Parallel port header (LPT)
	AMI BIOS with 128 MB SPI Flash ROM
	Supports M.I.B III Utility
SYSTEM BIOS	F7 hot key for boot up devices option
	Dual Display
	Support GUI UEFI BIOS
	Multi-Language BIOS
FORM FACTOR	Mini ITX Form Factor
OS Support	170*170
	Windows 10 64-bit
	CE/FCC Certification
Certifications	ErP/EuP Certification
	WHQL Certification