

589.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel LGA1200 !



Support:  [Datasheet](#)

- Intel® LGA1200 socket 10/11th Gen Core™ Processors
- 2* DDR4 2666/2400MHz SO-DIMM up to 64GB
- 3* USB 3.2 (Type A/Gen2), 1* USB 3.2 (Type C/Gen1), 4* USB2.0, 1* GbE, 1* COM
- 1* HDMI1.4, 1* DP
- DC-19V_120W Adapter

| | | | |
|---------------|--|---------------------|--|
| Dimensions | – 264 (W) x 199.4 (D) x 38 (H) mm | | |
| MB model | – MI09-H470 / Mini ITX (6.7-in * 6.7-in, 170 * 170mm) | | |
| Part No | Non-Wifi | Wifi | |
| | – HBJC511I09-H470-B | – HBJC511I09-H470-B | |
| CPU/Chipset | – Intel® 10/11th LGA 1200 Socket Core i9/i7/i5/i3/Pentium/Celeron Comet Lake-S/Rocket Lake-S Processor (Max:35W) – Intel® H470 chipset Notes: When the system runs, CPU will automatically adjust its working clock frequency according to changing workload. | | |
| BIOS | – AMI SMT Flash ROM | | |
| Memory | – 2* DDR4 2666/2400MHz SO-DIMM up to 64GB | | |
| Network | – 1* Intel i219V GbE – 1* M.2 E-key Slot 2230 (For WiFi/BT Modul, support CNVi) | | |
| Storage | – 1* 2.5" SATA3 6Gb/s internal drive bay – 1* M.2 M-Key (2260/2280, SATA/PCIe) | | |
| Expansion | – 1* M.2-2230 E-Key (for WIFI, Optional) | | |
| Rear I/O Port | – 3* USB 3.2 (Type A/Gen2) – 1* USB 3.2 (Type C/Gen1) – 1* HDMI 1.4 (Max Resolution: 4096x2160@30Hz) – 1* DP (Max Resolution: 4096x2304@60Hz) – 1* RJ45 (Intel i219V GbE) – 1* COM (RS232) – 1* Line-out, 1* Mic-in – 2* Antenna holes (WiFi only) – 1* DC-In Jack | | |

| | |
|-------------------|---|
| Front I/O Port | <ul style="list-style-type: none"> - 1* Power button, 1* Reset button - 1* Power LED, 1* HDD LED - 1* Line-out, 1* MIC - 4* USB 2.0 |
| Internal I/O Port | <ul style="list-style-type: none"> - 1* SIM Card holder - 1* M.2-3042 B-Key slot |
| Power Source | <ul style="list-style-type: none"> - AC 90~240V input / DC19V_120W output - MI09 MB : 12~19V DC-in |
| Certification | <ul style="list-style-type: none"> - CE, FCC, RoHS, ErP Ready |
| Environment | <ul style="list-style-type: none"> - Operating Temperature : 0°C~50°C - Storage Temperature : -20°C~70°C - Humidity: 10% ~ 90% RH @40°C (non-condensing) |
| Packing | <ul style="list-style-type: none"> - Net Weight■2.4 KG - Gross Weight■3.4 KG - Color Box Dimension■406(W) x 3148(D) x 380(H) mm |